

LR Display Receivers for Grading and Excavating



Laser Display System Benefits

- Allows operator to check grade from the cab; increases productivity and safety and reduces labor
- Reduces rework because material is moved only one time
- Increases overall operator and machine efficiency, saving fuel and time
- Can easily and quickly be moved from one machine to another
- Wireless remote capability
- Works with your existing rotating laser - no longer need a second person with a rod mounted laser receiver

Getting to Grade Faster Increases Operator and Machine Productivity

Spectra Precision® LR Display Systems let you spend less time walking the job site ... and more time in the cab being productive. The laser display receiver guides the operator to the desired elevation or depth without a grade checker. Your accuracy will improve and your profits will increase. The operator optimizes machine time, effectiveness, efficiency and increases safety.

You can use these rugged, highly flexible display systems on a wide range of machines. The receivers are self-contained, portable and easily moved from machine to machine for greater operator and machine efficiency.

A wireless remote display and quick mounting accessories add to the versatility of the receivers.

Used on

- Backhoes
- Excavators
- Skid Steer Attachments
- Box Blades
- Dozers
- Trenchers



Tough, Affordable Spectra Precision Laser Machine



LR20 for Grade and Depth Control

Ideal for use on mini-excavators and compact machines

- 8-inch, 360-degree laser reception provides large working area and range
- Built in plumb indicator for fast, accurate grade checking in mini-excavator applications
- Super bright grade display with green "on-grade" LEDs provides superior depth/elevation indication
- Push button setup for ease of use and application flexibility
- System package with mini magnetic mount fits in compact carrying case for easy storage and transport
- Center and offset on-grades are ideal for both grading and excavating applications



LR30 for General Grading

Used on dozers and leveling equipment

- Use on grading equipment including dozers, scrapers, skid steers and levelers
- Five channels of grade information plus directional and out-of-beam indicator
- Three selectable accuracies meet job tolerances from rough grading to final finishing
- Full 360-degree reception picks up the laser from all directions
- LR30W links wirelessly to the RD20 in-cab display



LR50 for Excavating and Grading

Features built-in blade tilt and excavator boom plumb indicator

- Built-in blade tilt indicator helps the operator keep the blade level for increased accuracy and productivity
- Center On-grade provides an equal amount of grade information above and below on-grade. Use on dozers, graders, scrapers and box blades
- Built-in plumb indicator for fast, accurate grade checking in excavation applications
- Offset on-grade gives you more range above grade using the entire receiver for more productive excavation
- LR50W links wirelessly to the RD20 in-cab display



Spectra Precision Machine Display Receiver Features and Benefits

Versatile, 360-Degree Reception

Works with all types of rotating lasers and on all types of machinery for fast, no-hassle setup.

Multiple Accuracy Choices

Offers maximum flexibility to meet jobsite requirements, from rough grading to final finishing.

Wireless Remote Capability

Provides in-cab display of elevation and audible signals

Adjustable, Ultra-bright LED with Green On-Grade Display

Provides user selectable, easy-to-see display to match ambient lighting conditions.

Out-of-Laser Beam Indication

Indicator directs which way to move and get back in the beam. Selectable on or off.

Two-Year Warranty

Reliability you can count on.

Power Options

Choose alkaline batteries, nickel metal hydride rechargeable batteries, or a power cord that connects directly to the machine power.

Rugged & Waterproof

Durable polycarbonate and aluminum die cast housings withstand all weather and construction site conditions. Internal isolating shock mounts protect the electronics.

Accessories

RD20 Wireless Remote Display

Wireless remote mounts in the cab and displays grade information to the operator. Helps keep focus on the work and not on the receiver for higher productivity. Works with LR30W, LR50W & LR60W.



Display Receivers



LR60 for High Speed Excavating

Features **Angle Compensation for Excavating (ACE)** for accurate elevation readings without being plumb

- Patented Angle Compensation for Excavators automatically calculates and corrects the grade display for the angle of the dipper arm
- Check grade with the dipper arm extended or retracted up to 30 degrees
- Built-in plumb indicator for fast, accurate grade checking
- Large vertical reception height for use with bigger excavators
- Center On-grade provides an equal amount of grade information above and below on-grade. Use on dozers, graders, scrapers and box blades
- LR60W links wirelessly to RD20 in-cab display



Specifications	LR20	LR30 / LR30W
Number of Display Channels	5-Channel Display	5-Channel Display
Accuracy: Center on grade mode (grading)	Fine: 5 mm (0.20 in) Standard: 10 mm (0.40 in) Wide: 20 mm (0.80 in)	Fine: 5 mm (0.20 in) Standard: 12 mm (0.45 in) Wide: 32 mm (1.25 in)
Accuracy: offset on grade mode (excavating)	Fine: 12 mm (0.50 in) Standard: 25 mm (1.0 in) Wide: 50 mm (2.0 in)	NA
ACE—Angle Compensation Mode	NA	NA
Blade-Tilt Accuracy	NA	NA
Plumb-Swing Accuracy	± 0.5°, ± 1.5°, ± 2.5°	NA
Vertical Reception	203 mm (8 in)	171 mm (6.75 in)
LED Battery Life		
Alkaline Bright/Dim		50 / 75 hrs
Wireless with remote on		30 / 40 hrs
Ni-MH Bright/Dim	35hrs	40 / 50 hrs
Wireless with remote on		20 / 30 hrs
Receiver Warranty	2 Years	2 Years

Specifications	LR50 / LR50W	LR60 / LR60W
Number of Display Channels	5-Channel Display 6-Channel Display in excavating mode	9-Channel Display
Accuracy: Center on grade mode (grading)	Fine: 5 mm (0.20 in) Standard: 10 mm (0.40 in) Wide: 20 mm (0.80 in)	Setup: 5 mm (0.20 in) Fine: 10 mm (0.40 in) Standard: 20 mm (0.80 in) Wide: 40 mm (1.6 in)
Accuracy: offset on grade mode (excavating)	Fine: 12 mm (0.50 in) Standard: 25 mm (1.0 in) Wide: 50 mm (2.0 in)	Setup: 6 mm (0.25 in) Fine: 12 mm (0.50 in) Standard: 25 mm (1.0 in) Wide: 50 mm (2.0 in)
ACE—Angle Compensation Mode	NA	Fine: 12 mm (0.50 in) Standard: 25 mm (1.0 in)
Blade-Tilt Accuracy	± 0.5°, ± 1.5°, ± 2.5°	N/A
Plumb-Swing Accuracy	± 0.5°, ± 1.5°, ± 2.5°	Standard: (12 mm 0.5 in) ACE Mode: 25 mm (1.0 in)
Vertical Reception	171 mm (6.75 in)	222 mm (8.75 in)
LED Battery Life		
Alkaline Bright/Dim	45 / 60 hrs	45 / 75 hrs
Wireless with remote on	20 / 30 hrs	35 / 25 hrs
Ni-MH Bright/Dim	30 / 45 hrs	40 / 50 hrs
Wireless with remote on	15 / 20 hrs	25 / 20 hrs
Receiver Warranty	2 Years	2 Years

MM-1 Magnetic Mount

The MM-1 quickly attaches to the dipper arms of excavators or backhoes. Strong dual magnet packs will not slip on the machine and are adjustable for quick installation and set-up.



DM-20 Dozer Mast

The DM-20 is an easy-to-install rigid mast for grading machines. No welding is required and no drilling/tapping is required for Trimble Ready™ machines.



Rugged Laser Transmitters Built for the Jobsite



LL300S Laser Level

Fast setup, automatic electronic self leveling and long range Rugged design - Warranted to withstand 1 m (3 ft) drop

Applications

- Level and manual slope work
- General elevation control
- Cut and fill



LL500 Laser Level

Long range accuracy and field proven reliability The workhorse of the industry for decades

Applications

- Level work
- General elevation control
- General construction
- Cut and fill



GL412N/GL422N Grade Lasers

Powerful, easy-to-use single or dual slope grade lasers with radio remote Three lasers in one - Level, grade, and vertical alignment

Applications

- Level and automatic slope (grade) work
- Site preparation
- General construction



GL612/GL622 Grade Lasers

Accurate horizontal, vertical, single or dual slope grade lasers with radio remote Automatic Grade Match and Pannelok functions, for precision concrete applications

Applications

- Leveling concrete forms
- Grade/elevation control
- Remote elevation monitoring (HL750 receivers)



UL633 Universal Laser

Versatile grade laser with total control in X, Y and Z axes Automatic Pannelok functions for precision concrete laser screed applications

Applications

- Leveling concrete forms
- Grade/elevation control
- Machine control
- Pipe laying and layout

Specifications	LL300S	LL500	GL412N/GL422N	GL612N/GL622N	UL633N
Level Accuracy	1.5 mm @ 30 m (1/16" @ 100 ft) 10 arc seconds	1.5 mm @ 30 m (1/16" @ 100 ft) 10 arc seconds	1.5 mm @ 30 m (1/16" @ 100 ft) 10 arc seconds	1.5 mm @ 30 m (1/16" @ 100 ft) 10 arc seconds	1.5 mm @ 30 m (1/16" @ 100 ft) 10 arc seconds
Grade Range	Manual	N/A	-10 to +15% Single / Dual Axis	-25 to +25% Single / Dual Axes	-25 to +25% 3 Axes
Operating Diameter	800 m (2600 ft)	500 m (1600 ft)	800 m (2600 ft)	800 m (2600 ft)	800 m (2600 ft)
Temperature Compensation	Yes	No	Yes	Yes	Yes
Laser Type / Classification	3 mW 650 nm, Class 2	3 mW 670 nm, Class 2	3 mW 650 nm, Class 2	3 mW 650 nm, Class 2	<5 mW 650 nm, Class 3A/3R
Rotation Speed	600 rpm	600 rpm	300, 600 rpm	GL612N: 300, 600 750 rpm GL622N: 0 to 900 rpm	0 - 750 rpm
Battery Life	Alkaline - 60 hrs Ni-MH - 47 hrs (Optional)	Alkaline - 170 hrs Ni-MH - 100 hrs (Optional)	Alkaline - 50 hrs Ni-MH - 35 hrs (Standard)	Alkaline - 40 hrs Ni-MH - 35 hrs (Standard)	Alkaline - 40 hrs Ni-MH - 35 hrs (Standard)
Drop Height on Concrete	1 m (3 ft)	N/A	1 m (3 ft)	1 m (3 ft)	1 m (3 ft)
Laser Warranty	5 Years	5 Years	5 Years	5 Years	5 Years
Standard Receiver	Choice of HL450 or HL760 Digital Readout receiver	Choice of HL700 Digital Readout receiver or CR600 combo receiver	Choice of HL760 Digital Readout receiver or CR600 receiver	HL760 Digital Readout receiver	2 x HL760 Digital Readout receiver
Standard Receiver Warranty	5 Years	5 Years	5 Years	5 Years	5 Years
Wireless Remote Receiver Elevation Monitoring (HL750/HL760 receiver)	Yes	N/A	Yes	Yes	Yes
Operating Temperature	-20° to +50°C (-4° to +122°F)	-20° to +50°C (-4° to +122°F)	-20° to +50°C (-4° to +122°F)	-20° to +50°C (-4° to +122°F)	-20° to +50°C (-4° to +122°F)
Remote Control	Optional RC402N	N/A	RC402N Full 2-way communication	RC602 Full 2-way communication	RC603 Full 2-way communication
Remote Operating Range	100 m (330 ft) radius	N/A	100 m (330 ft) radius	100 m (330 ft) radius	100 m (330 ft) radius

www.sitech-ches.com

SITECH - Annapolis Junction
12011 Guildford Rd Ste. 109
Annapolis Junction, MD 20701
(443) 579-3400
Hours: M-F 7:30AM-4:30PM

SITECH - Ashland
10966 S. Richardson Road, Ste. H
Ashland, VA 23005
(804) 752-7522
Hours: M-F 8AM-5PM

SITECH - Chesapeake
1226 Executive Blvd #120
Chesapeake, VA 23320
(757) 548-8100
Hours: M-F 7:30AM-4PM

